

ContentKeeper VLE



Intel® Dual Xeon™ 2U Rackmount Network Security Appliance with 6 PCI-E/Gigabit LAN



Main Features

- ♦ High CPU Computing Power with Intel® Dual Xeon™ EM64T up to 3.6 GHz
- ♦ Dual Channel DDR2 400 Memory up to 8 GB
- ♦ Modular Design Supports Two PCI-E Modules (PCI-E x 8 Interface)
- ♦ Flexible Port Configuration Supports Copper/SFP GbE LAN
- ♦ Line Fault Tolerance Design with Copper GbE Bypass
- ♦ PCI-X Expansion for Network Acceleration Card
- ♦ I/O Module Supports Programmable Reset Switch and Serial RJ45 Console
- ♦ Supports On-board CF Socket and LCD Module
- ♦ Supports Dual 3.5" Serial-ATA or ATA-133 HDD
- ♦ Supports Redundant Power Supplies
- ♦ LCD Module

Specifications

CPU

- ♦ Intel® Dual Xeon™ EM64T with 800 MHz FSB

RAM Type & Max. Capacity

- ♦ 8 GB (DDR2 400)
- ♦ DIMM x 4
- ♦ ECC & Registered Only

Chipset

- ♦ Intel® E7520 + 6300ESB

LAN Chip

- ♦ Intel® 82571EB (Copper), 82546GB (Fiber)

10/100/1000 LAN

- ♦ 4 ports (RJ45), 2 ports (SFP)

10/100 LAN

- ♦ 1 (For management)

HDD

- ♦ Support two 3.5" HDD Bay

CF

- ♦ 1

LAN Bypass

- ♦ GbE LAN Bypass

Serial

- ♦ 2 (RJ45 Connectors)

IDE /SATA

- ♦ 1 / 2

USB

- ♦ 2 at Front

PCI Expansion

- ♦ PCI-X slots x 2

LCM Module

- ♦ 2 x 16, PIO

Indicators

- ♦ Power x 1, HDD x 1, Customer programmable x 2

Power

- ♦ 460 W ATX Redundant PSU

Form Factor

- ♦ 2 U

Dimensions

- ♦ 424 x 530 x 88 mm

Certifications

- ♦ CE
- ♦ FCC Class A

Carton Dimensions

- ♦ 620 x 730 x 300 mm

Net Weight

- ♦ 18 kg

Ordering information

- ♦ NSA 2067RL
2U Rackmount Chassis, 6 port GbE
I/O: COM Port x 2 and USB Port x 2
Compact Flash x 1
With LCM Module x 1
Redundant Power Supply: 460 W